

Eco Rotator

Hunter®



Ecology + Economy

Want to keep it green while saving resources? Get to know the Eco Rotator. You get an eco-nomical, eco-logical choice that minimizes water use and installation time and maximizes flexibility and performance.

This compact sprinkler comes with a pre-installed MP Rotator, providing up to a 30 percent water savings over traditional nozzles. Add that to a spray body with a reliable two-piece ratchet, durable cap, and large filter screen with double filtration, and you have a tough combination to beat.



ECO ROTATOR

Multi-trajectory rotating streams are wind resistant, apply water slower, and use 30 percent less water than conventional sprays

Double filtered for double the debris protection

Eco Rotator has matched application rates at any radius or arc

Strong body cap for long life and easy installation

Two-piece ratchet for dependable and reliable performance



Charts and Specs

Eco Rotator Performance Data – Metric																				
ECO-04-1090 Radius: 2.5 to 4.6 m Adjustable Arc and Full Circle Color Code: Maroon																				
Arc	Pressure		Color	Radius m	Flow LPH	Flow LPM	Precip mm/hr		ECO-04-2090 Radius: 4 to 6.4 m Adjustable Arc and Full Circle Color Code: Black											
	Bars	kPa					■	▲	Color	Radius m	Flow LPH	Flow LPM	■	▲	■	▲				
90°	1.75	175	Maroon = 90° to 210°	---	---	---	---	---	Black = 90° to 210°	4.9	133	2.22	11	12	Blue = 90° to 210°	7.6	158	2.63	11	13
	2.00	200		3.7	36	0.61	11	12		5.2	71	1.18	11	12		8.2	166	2.77	10	11
	2.25	225		3.8	38	0.63	10	12		5.6	80	1.33	10	12		8.4	175	2.92	10	12
	2.50	250		4.0	41	0.68	10	12		5.8	86	1.43	10	12		8.5	185	3.08	10	12
	2.75	275		4.1	42	0.70	10	11		6.1	91	1.52	10	11		9.1	195	3.25	9	11
	3.00	300		4.3	44	0.73	10	11		6.4	94	1.57	9	11		9.1	203	3.38	10	11
	3.25	325		4.3	45	0.75	10	11		6.6	97	1.62	9	10		9.1	212	3.53	10	12
180°	3.50	350	4.4	47	0.78	10	11	6.7	101	1.68	9	10	9.1	220	3.67	11	12			
	3.75	375	4.6	49	0.81	9	11	6.7	106	1.77	9	11	9.1	228	3.80	11	13			
	1.75	175	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	
	2.00	200	3.7	72	1.20	11	12	5.2	141	2.35	11	13	8.2	353	5.88	10	12			
	2.25	225	3.8	76	1.27	10	12	5.3	150	2.50	11	13	8.4	373	6.22	11	12			
	2.50	250	4.0	81	1.35	10	12	5.5	160	2.67	11	12	8.5	393	6.55	11	12			
	2.75	275	4.1	84	1.40	10	11	5.8	168	2.80	10	12	9.1	413	6.88	10	11			
210°	3.00	300	4.3	88	1.46	10	11	6.1	174	2.90	10	11	9.1	431	7.18	10	12			
	3.25	325	4.3	91	1.51	10	11	6.2	182	3.03	9	11	9.1	449	7.48	11	12			
	3.50	350	4.4	94	1.56	10	11	6.4	189	3.15	9	10	9.1	466	7.77	11	13			
	3.75	375	4.6	97	1.62	9	11	6.4	193	3.22	9	11	9.1	481	8.02	12	13			
	1.75	175	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---		
	2.00	200	3.7	85	1.41	11	13	4.9	155	2.58	11	12	7.6	384	6.40	11	13			
	2.25	225	3.8	89	1.48	10	12	5.2	165	2.75	11	13	8.2	411	6.85	10	12			

SPECIFICATIONBUILDER

MODEL	FEATURES	OPTIONS
ECO (½" female inlet)	04 = 10 cm (4") Pop-up	1090 = MP1000 90° to 210° 2090 = MP2000 90° to 210° 3090 = MP3000 90° to 210°
▶ ECO	▶ 04	▶ 1090
EXAMPLE	▶ ECO - 04 - 1090	