



SAFETY DATA SHEET

According to Safe Work Australia

Printing date 01.04.2015

Revision: 01.04.2015

1. IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

Product Name: WELD-ON® 725™ WET 'R DRY™ LOW VOC CEMENT FOR PVC PLASTIC PIPE

Other Means of Identification: Mixture

Recommended Use of the Chemical and Restriction on Use:

Low VOC Solvent Cement for CPVC Plastic Pipe

Details of Manufacturer or Importer:

HR Products
207 Bannister Road
Canning Vale WA 6155

Phone Number: 08 9455 1677

Emergency telephone number: 0413 700 807

2. HAZARDS IDENTIFICATION

Hazardous Nature:

Classified as Hazardous according to criteria of National Occupational Health & Safety Commission (NOHSC), Australia.

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition).



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

Carc. 2 H351 Suspected of causing cancer.



Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Signal Word Danger

Hazard Statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P240 Ground/bond container and receiving equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

(Contd. on page 2)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 01.04.2015

Revision: 01.04.2015

Product Name: WELD-ON® 725™ WET 'R DRY™ LOW VOC CEMENT FOR PVC PLASTIC PIPE

(Contd. of page 1)

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use for extinction: CO2, powder or water spray.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national regulations.

Additional Information

AUH001 Explosive when dry.

AUH019 May form explosive peroxides.

3 . COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical Characterization: Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.**Hazardous Components:**

Hazardous Components:		
109-99-9	tetrahydrofuran ⚠ Flam. Liq. 2, H225; ⚠ Carc. 2, H351; ⚠ Eye Irrit. 2A, H319; STOT SE 3, H335	45-60%
67-64-1	Acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	14-25%
78-93-3	2-Butanone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	4-15%

Additional information: For the wording of the listed risk phrases refer to section 16.

4 . FIRST AID MEASURES

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if breathing problems develop.

Skin Contact:

In case of skin contact, immediately remove contaminated clothing and wash affected areas with water and soap. Seek medical attention if symptoms occur.

Eye Contact:

In case of eye contact, rinse with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek immediate medical attention.

Ingestion:

If swallowed, do not induce vomiting. Immediately rinse mouth with water. Give 1 or 2 glasses of water or milk to dilute. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Symptoms Caused by Exposure:

Inhalation: May cause respiratory irritation. Severe overexposure may result in nausea, dizziness, drowsiness and headache.

Skin Contact: Liquid contact may remove natural skin oils resulting in skin irritation.

Eye Contact: Causes serious eye irritation. Overexposure may result in corneal or conjunctival inflammation

(Contd. on page 3)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 01.04.2015

Revision: 01.04.2015

Product Name: WELD-ON® 725™ WET 'R DRY™ LOW VOC CEMENT FOR PVC PLASTIC PIPE

(Contd. of page 2)

on contact with the liquid.

Ingestion: May cause nausea, vomiting, diarrhoea and mental sluggishness.

5 . FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Dry chemical powder, carbon dioxide gas, foam, halon and water fog. Do not use water jet.

Specific Hazards Arising from the Chemical:

Hazardous combustion products include oxides of carbon and smoke.

Product is highly flammable. Vapours may travel considerable distances to a source of ignition where they can ignite, flashback, or explode.

Closed containers may explode when exposed to extreme heat. Containers close to fire should be removed if safe to do so. Use water spray to cool fire exposed containers.

Special Protective Equipment and Precautions for Fire Fighters:

Wear Safe Work Australia approved self-contained breathing apparatus and full protective clothing.

6 . ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:

Wear Safe Work Australia approved respiratory protection and other suitable protective equipment. Evacuate all non-essential personnel from affected area. Do not breathe vapours. Ensure adequate ventilation. Extinguish all sources of ignition. Avoid sparks and open flames. No smoking.

Environmental Precautions:

In the event of a major spill, prevent spillage from entering drains or water courses.

Methods and Materials for Containment and Cleaning Up:

Stop leak if safe to do so and absorb spill with sand, earth, vermiculite or some other absorbent material. Collect the spilled material and place into a closable metal container for disposal. Do not use aluminium or plastic containers. Use only non-sparking tools.

7 . HANDLING AND STORAGE

Precautions for Safe Handling:

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of vapours. Use only outdoors or in a well-ventilated area.

Take precautionary measures against static discharge. Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

Conditions for Safe Storage:

Store in a cool, dry and well ventilated area. Keep container tightly closed when not in use. Do not expose to temperatures exceeding 27 °C. Protect from heat, sparks, open flames and other sources of ignition. Keep away from strong oxidising agents, caustics, ammonia, inorganic acids, chlorinated compounds and isocyanates. Do not weld, cut or drill on full or empty containers. Handling equipment must be grounded to prevent sparking.

8 . EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Standards:**109-99-9 tetrahydrofuran**

NES	TWA: 295 mg/m ³ , 100 ppm
	Sk

(Contd. on page 4)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 01.04.2015

Revision: 01.04.2015

Product Name: WELD-ON® 725™ WET 'R DRY™ LOW VOC CEMENT FOR PVC PLASTIC PIPE

(Contd. of page 3)

67-64-1 Acetone	
NES	STEL: 2375 mg/m ³ , 1000 ppm TWA: 1185 mg/m ³ , 500 ppm
78-93-3 2-Butanone	
NES	STEL: 890 mg/m ³ , 300 ppm TWA: 445 mg/m ³ , 150 ppm

Engineering Controls:

Maintain air concentration below occupational exposure standards, providing adequate ventilation. Use explosion-proof ventilating equipment.

Respiratory Protection:

If use conditions generate vapours or mists use respirator with a full face piece or a purifying cartridge respirator equipped for organic vapours and mists, a self contained breathing apparatus in the pressure demand mode or a positive pressure air-supplied respirator. See Australian Standards AS/NZS 1715 and 1716 for more information.

Skin Protection:

PVA, nitrile, neoprene, latex, rubber or vinyl gloves. See Australian/New Zealand Standard AS/NZS 2161 for more information. When selecting gloves for use against certain chemicals, the degradation resistance, permeation rate and permeation breakthrough time should be considered. Solvent-resistant barrier creams may also be used. Occupational protective clothing (depending on conditions in which it has to be used, in particular as regards the period for which it is worn, which shall be determined on the basis of the seriousness of the risk, the frequency of exposure to the risk, the characteristics of the workstation of each worker and the performance of the protective clothing). See Australian/New Zealand Standard AS/NZS 4501 for more information.

Eye and Face Protection:

Eye and face protectors for protection against splashing materials or liquids. See Australian/New Zealand Standard AS/NZS 1337.

9 . PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Form:	Medium syrupy liquid
Colour:	Aqua blue
Odour:	Ketone
Odour Threshold:	0.88 ppm (Cyclohexanone)
pH-Value:	Not applicable
Melting point/Melting range:	-108.5 °C (Tetrahydrofuran)
Initial Boiling Point/Boiling Range:	56 °C (Acetone)
Flash Point:	-20 °C (TCC - Acetone)
Flammability:	Highly flammable.
Auto-ignition Temperature:	321 °C (Tetrahydrofuran)
Decomposition Temperature:	Not applicable
Explosion Limits:	
Lower:	1.4 Vol %
Upper:	12.8 Vol %
Vapour Pressure at 20 °C:	190 mmHg (Acetone)
Relative Density at 23 °C:	0.924
Vapour Density:	>2.0
Evaporation Rate:	>1.0
Solubility in Water:	Solvent portion completely soluble in water. Resin portion separates out.
Viscosity:	Medium bodied

(Contd. on page 5)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 01.04.2015

Revision: 01.04.2015

Product Name: WELD-ON® 725™ WET 'R DRY™ LOW VOC CEMENT FOR PVC PLASTIC PIPE

(Contd. of page 4)

VOC: = <510 g/L

10 . STABILITY AND REACTIVITY

Possibility of Hazardous Reactions: Hazardous polymerisation will not occur.

Chemical Stability: Stable at ambient temperature and under normal conditions of use.

Conditions to Avoid: Heat, sparks, open flames and other sources of ignition.

Incompatible Materials:

Strong oxidising agents, caustics, ammonia, inorganic acids, chlorinated compounds and isocyanates.

Hazardous Decomposition Products: Oxides of carbon and smoke.

11 . TOXICOLOGICAL INFORMATION

Toxicity:
LD₅₀/LC₅₀ Values Relevant for Classification:
109-99-9 tetrahydrofuran

Oral	LD ₅₀	2880 mg/kg (rat)
Inhalation	LC ₅₀	21000 ppm (rat) (3 hour)

78-93-3 2-Butanone

Oral	LD ₅₀	3980 mg/kg (rat)
Dermal	LD ₅₀	8-10 mg/kg (rabbit)
Inhalation	LC ₅₀ /4 h	4000 ppm (rat)

67-64-1 Acetone

Oral	LD ₅₀	5800 mg/kg (rat)
Dermal	LD ₅₀	20000 mg/kg (rabbit)

Acute Health Effects
Inhalation:

May cause respiratory irritation. Severe overexposure may result in nausea, dizziness, drowsiness and headache.

Skin: Liquid contact may remove natural skin oils resulting in skin irritation.

Eye:

Causes serious eye irritation. Overexposure may result in corneal or conjunctival inflammation on contact with the liquid.

Ingestion: May cause nausea, vomiting, diarrhoea and mental sluggishness.

Skin Corrosion / Irritation: Based on classification principles, the classification criteria are not met.

Serious Eye Damage / Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitisation: Based on classification principles, the classification criteria are not met.

Germ Cell Mutagenicity: Based on classification principles, the classification criteria are not met.

Carcinogenicity:

Tetrahydrofuran is classified by Safe Work Australia as Carcinogen Category 3.

Suspected of causing cancer.

Cyclohexanone is classified by IARC as Group 3 - Not classifiable as to its carcinogenicity to humans.

Reproductive Toxicity: Based on classification principles, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) - Single Exposure:

May cause respiratory irritation.

(Contd. on page 6)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 01.04.2015

Revision: 01.04.2015

Product Name: WELD-ON® 725™ WET 'R DRY™ LOW VOC CEMENT FOR PVC PLASTIC PIPE

(Contd. of page 5)

May cause drowsiness and dizziness.

Specific Target Organ Toxicity (STOT) - Repeated Exposure:

Based on classification principles, the classification criteria are not met.

Aspiration Hazard: Based on classification principles, the classification criteria are not met.**Chronic Health Effects:**

Repeated exposure may cause skin dryness or cracking.

Low level chronic exposure to 2-Butanone has been shown to cause decreased memory and impairment of the central nervous system.

Existing Conditions Aggravated by Exposure: No information available**Additional toxicological information:** No information available**12 . ECOLOGICAL INFORMATION****Ecotoxicity:** No information available**Aquatic toxicity:****109-99-9 tetrahydrofuran**

EC50 382 mg/L - 24 h (daphnia)

LC50 2.160 mg/L - 96 h (fathead minnow)

Persistence and Degradability: This product is not readily biodegradable.**Bioaccumulative Potential:** No bioaccumulation is to be expected ($\log Pow \leq 4$).**Mobility in Soil:** No information available**Other adverse effects:** No information available**13 . DISPOSAL CONSIDERATIONS****Disposal Methods and Containers:** Dispose according to applicable local and state government regulations.**Special Precautions for Landfill or Incineration:**

Please consult your state Land Waste Management Authority for more information.

14 . TRANSPORT INFORMATION**UN Number****ADG, IMDG, IATA**

UN 1133

Proper Shipping Name**ADG, IMDG, IATA**

ADHESIVES

Dangerous Goods Class**ADG Class:**

3 Flammable liquids.

Packing Group:**ADG, IMDG, IATA**

II

Marine pollutant:

No

Hazchem Code:

.3YE

Special Provisions:

274

Limited Quantities:

5L

Packagings & IBCs - Packing Instruction:

P001, IBC02

(Contd. on page 7)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 01.04.2015

Revision: 01.04.2015

Product Name: WELD-ON® 725™ WET 'R DRY™ LOW VOC CEMENT FOR PVC PLASTIC PIPE

(Contd. of page 6)

Packagings & IBCs - Special Packing Provisions: PP1**Portable Tanks & Bulk Containers - Instructions: T4****Portable Tanks & Bulk Containers - Special Provisions: TP1, TP8**

15 . REGULATORY INFORMATION

Australian Inventory of Chemical Substances:

109-99-9	tetrahydrofuran
108-94-1	Cyclohexanone
78-93-3	2-Butanone

Standard for the Uniform Scheduling of Drugs and Poisons (SUSMP) - Poison Schedule:
Not Scheduled.

16 . OTHER INFORMATION

Creation Date: 01.04.2015**Prepared by:** MSDS.COM.AU Pty Ltdwww.msds.com.au

Abbreviations and acronyms:

ADG: Australian Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds

LC₅₀: Lethal concentration, 50 percentLD₅₀: Lethal dose, 50 percent

IARC: International Agency for Research on Cancer

STEL: Short Term Exposure Limit

TWA: Time Weighted Average

NES: National Exposure Standard (Safe Work Australia - Workplace Exposure Standards For Airborne Contaminants)

Disclaimer

This MSDS is prepared in accord with the Safe Work Australia document "Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals - December 2011"

The information contained in this material safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. HR Products makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.