**PRODUCT SPECIFICATION** 



## OdisMatic<sup>™</sup> Series 850 Hydraulic Filter

This automatic screen filter, hydraulically operated, is a perfect solution for use without power supply in irrigation, industry and recycling.

The filter has a specially effective suction nozzles system for cleaning the screen. The self-cleaning mechanism is hydraulically operated by the in line water pressure.

The cleaning process can be activated automatically or manually.

During flushing cycle the suction nozzles scan the entire screen's inner surface in a helical movement.

## Advantages:

- High Reliability: Maintains high filtering efficiency
- Low head-loss
- Efficient fully automatic self-cleaning mechanism
- Filter uses small quantities of water to flush the screen
- Filtered water supply is not interrupted during flushing
- Simple and easy to operate
- Low maintenance cost
- Low cost per cubic meter of filtered water
- Long service life thanks to anti corrosion protection coating and non corrosive materials



Model	Inlet / Outlet Diameter	Maximum Flow Rate m3/h	Flushing Flow Rate m3/hr	Screen Area cm2
85002-IE/PE	50mm	25	18-24	580
85003-IS/PS	80mm	40	18-24	580
85003-IE/PE	80mm	40	18-24	2150
85004-IS/PE	100mm	80	28-34	1100
85004-IE/PE	100mm	80	27-36	4300
85006-IE/PE	150mm	150	27-36	4300
85008-IS/PS	200mm	300	27-36	4300
85008-PE	200mm	300	36-48	6550
8510-IS/PS	250mm	400	27-36	5750
85012-IS/PS	250mm	600	34-48	8550

Specifications subject to change without notice – Product drawings / images are representative only and are subject to change.

PERTH PH: 08 9455 1677 FAX: 08 9455 1680 hrsales@hrproducts.com.au SYDNEY PH: 02 9725 5733 FAX: 02 725 5283 nfonsw@hrproducts.com.au MELBOURNE PH: 03 9457 7500 FAX: 03 9457 7400

BRISBANE PH: 07 3806 0522 FAX: 07 3806 0533 ADELAIDE PH: 08 8341 0008 FAX: 08 8341 0707 infosa@hrproducts.com.au

www.hrproducts.com.au

