

MINI-CLIK®

Application: **Residential/Commercial**
 Sensor: **Rain**

FEATURES

- Easily installs on any automatic irrigation system
- Debris tolerant for reliable operation and no unnecessary shutdowns
- Can be set to shut system off from 3 mm to 25 mm of rainfall
- Includes 7.6 m of 0.5 mm² (20 AWG) sheathed, two-conductor, UL-approved wire
- Optional user-installed metal gutter mount for Mini-Clik® (order SGM)
- Warranty period: 5 years

ELECTRICAL SPECIFICATIONS

- Switch rating: 24 VAC, 5 A
- Wiring: 0.5 mm² (20 AWG), UL listed, typically interrupts the common ground wire between the solenoid valves and controller



MINI-CLIK
8 cm H x 15 cm L



SGM
Optional gutter mount



SG-MC
Stainless steel sensor guard enclosure for Mini-Clik

MINI-CLIK®	
Model	Description
MINI-CLIK	Rain Sensor
MINI-CLIK-NO	Rain Sensor w/ normally open switch
MINI-CLIK-C	Rain Sensor w/ conduit mount
MINI-CLIK-HV	Rain Sensor for high voltage application (120/240 VAC)

USER INSTALLED OPTIONS (Specify Separately)	
Model	Description
SGM	Optional Gutter Mount
SG-MC	Stainless Steel Sensor Guard Enclosure for Mini-Clik