

RAIN-CLIK™

Application: **Residential/Commercial**

Sensor: **Rain**

FEATURES

- Quick Response™ feature shuts the system off as soon as it starts raining
- Maintenance-free design with 10-year battery life for Wireless Rain-Clik
- Adjustable vent ring allows for setting of reset delay
- Rugged polycarbonate housing and metal extension arm
- Rain-Clik includes 7.6 m of 0.5 mm² (20 AWG) sheathed, two-conductor, UL-approved wire
- Wireless unit available with 244 m range from wireless sensor to receiver
- Compatible with most controllers
- Warranty period: 5 years (10 year battery warranty for wireless model)

ELECTRICAL SPECIFICATIONS

- Wiring: normally closed or normally open
- Time to turn off irrigation system: 2 to 5 minutes approx. for Quick Response
- Time to reset Quick Response: 4 hours approx. under dry, sunny conditions
- Time to reset when fully wet: 3 days approx. under dry, sunny conditions
- Switch rating: 24 VAC, 3 A
- Freeze sensor shuts system off when temperatures fall below 3° C (Rain/Freeze-Clik model)
- System operating frequency: 433 MHz (Wireless model)
- UL listed, FCC approved, suitable for use in Australia, CUL (CSA), CE
- Communication range up to 244 m line of sight (Wireless model)
- Rain/Freeze-Clik shuts system off when temperatures fall below 3° C
- Receiver input power: 24 VAC (from controller)



RAIN-CLIK
6.4 cm H x 18 cm L



WR-CLIK (transmitter)
7.6 cm H x 20 cm L



WR-CLIK (receiver)
8.3 cm W x 10 cm H



SGM
Optional gutter mount

SENSORS

RAIN-CLIK™

Model	Description
RAIN-CLIK	Rain-Clik sensor
RFC	Rain/Freeze-Clik sensor
WR-CLIK	Wireless Rain-Clik system
WRF-CLIK	Wireless Rain/Freeze-Clik system

USER INSTALLED OPTION (Specify Separately)

Model	Description
SGM	Optional gutter mount (included in the WRF-CLIK)