



Single piece 360° stream open spray jet engineered for high performance at an affordable price.

### Features

- Colour coded for flow rate identification.
- 12 Stream Hi-Lo watering pattern (a).
- Robust proven C-Frame design.
- No moving parts.
- "Quick" thread inlet with sealing barb.


### Applications

Specifically designed for orchards and horticultural crops.

### Accessories


Asta® Stake, Rigid Riser and Micro Stake.

### Performance Chart

Pattern/ Trajectory	360° x 12 Streams - Hi Lo (a) 					
	26° High x 12.5° Low Trajectory					
Tested at 0.2 m above ground						
Nozzle Size & Colour	Pressure (kPa)	Flow (lph)	Diameter - (m)		Hydraulic Flow Data	
			High	Low	Constant (k)	Exponent (x)
0.8 mm Black	50	16	2.6	2.0	2.464	0.48
	100	22	3.5	2.8		
	150	27	4.2	3.4		
	200	31	4.8	3.9		
	250	35	5.3	4.4		
0.9 mm Orange	50	20	3.1	2.3	2.589	0.52
	100	28	4.1	3.1		
	150	35	4.8	3.8		
	200	41	5.3	4.4		
	250	46	5.8	4.9		
1.0 mm Blue	50	24	3.4	2.4	3.479	0.49
	100	33	4.2	3.4		
	150	41	4.8	4.1		
	200	47	5.3	4.7		
	250	52	5.6	5.2		
1.1 mm Purple	50	31	4.1	3.2	4.196	0.51
	100	44	5.3	4.2		
	150	54	6.0	4.9		
	200	63	6.6	5.5		
	250	70	7.2	6.0		
1.5 mm Red	50	51	5.5	4.3	6.634	0.52
	100	73	6.9	5.6		
	150	90	7.9	6.5		
	200	104	8.8	7.3		
	250	117	9.4	8.0		



CFa AgSpray™ Range



Typical System



CFa AgSpray™ on Micro Stake with 600 mm Tube and Adaptor

### Ordering Information - CFa AgSpray™

Nozzle Size & Colour	Order Code	Pack Quantity	Packs per Carton	Carton (kg)
0.8 mm Black	13005	100	90	15.0
0.9 mm Orange	13075	100	90	15.0
1.0 mm Blue	13015	100	90	15.0
1.1 mm Purple	13065	100	90	15.0
1.5 mm Red	13055	100	90	15.0

### Ordering Information - CFa AgSpray™ on Micro Stake w/ 600mm Tube & Adaptor

Nozzle Size & Colour	Order Code	Pack Quantity	Packs per Carton	Carton (kg)
0.8 mm	41605	25	5	6.9
0.9 mm	41675	25	5	6.9
1.0 mm	41615	25	5	6.9
1.1 mm	41665	25	5	6.9
1.5 mm	41655	25	5	6.9

### Specifications

Dimensions		UV Stabilised Material	Base/Connection Type	
HEIGHT	34 mm	acetal	Inlet	'QUICK' THREAD with sealing barb 4 mm
WIDTH	25 mm			
DEPTH	8 mm			
WEIGHT (approx.)	1.4 g			