



PRODUCT SPECIFICATION

FITTINGS

TAVLIT THREADED FITTINGS

High quality Polypropylene fittings for irrigation.

FEATURES

- Extra strong design and excellent mechanical properties for long life, durability and resistance to breakage
- Wide grip for easy assembly
- Tavlit threaded fittings are available with the unique self seal system (pre-assembled o-rings) that saves labour and allows tightening without tools

SPECIFICATION

- Material: Polypropylene
- O-Ring: EPDM
- Maximum operating pressure: 1600 kPa at 20°C
- Maximum working temperature: 100°C
- Threads: BSP
- 15mm to 50mm sizes available
- O-Ring seal on male and female ends of fittings

					
HEX NIPPLE	REDUCING HEX NIPPLE	REDUCING HEX BUSH	PLUG	TEE	90° ELBOW
					
90° M/F ELBOW	CAP	M/F REDUCING ADAPTOR	COUPLING	REDUCING COUPLING	IMPACT SPRINKLER COUPLING

Specifications Subject to Change Without Notice - Product Drawings / Images are representative only and are subject to change

FITTINGS_TAVLIT THREAD_V1.01.23

www.hrproducts.com.au



PERTH

PH: 08 9484 6500

FAX: 08 9455 1680

hrsales@hrproducts.com.au

SYDNEY

PH: 02 9616 1300

FAX: 02 9725 5283

infonsw@hrproducts.com.au

MELBOURNE

PH: 03 8458 7400

FAX: 03 9457 7400

infovic@hrproducts.com.au

BRISBANE

PH: 07 3080 6200

FAX: 07 3806 0533

infoqld@hrproducts.com.au

ADELAIDE

PH: 08 8408 7200

FAX: 08 8341 0707

infosa@hrproducts.com.au