

Putting Water Where it Counts!®



Joiners, Elbows, Tees & Crosses

Made in Australia

antelco.com

Tees & Crosses

A range of polypropylene Tees and Crosses designed to control, disperse, slow and divert water through a low pressure irrigation system. Used in conjunction with low density polyethylene (LDPE) tubing.

Features

- Tapered entry on all barbed fittings for ease of installation.
- Threaded Tees for sprinkler systems.
- Range suits Metric tube sizes and common drip tube sizes.
- UV stabilised materials for long life.
- Operating pressure range up to 300 kPa.



Applications

Home gardens, landscaping and commercially installed irrigation systems. **Accessories:** Ratchet Clamps and Stainless Steel Clamp.

Ordering Information - Tees

Type	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
Tee 13 mm	45035	25	48	6.3
Tee 19 mm	45065	25	22	5.3
Tee 25 mm	45075	25	8	4.8
Tee 32 mm	45085	25	4	3.7
Reducing Tee 19 mm line x 13 mm branch	45105	25	24	5.2
Reducing Tee 21 mm line x 19 mm branch	46255	25	18	5.4
Reducing Tee 25 mm line x 13 mm branch	45115	25	11	5.3
Reducing Tee 25 mm line x 19 mm branch	45125	25	10	5.3
Reducing Tee 32 mm line x 25 mm branch	45135	25	5	4.0
Threaded Tee 13 mm x 1/2" BSPF	45155	25	18	6.9
Threaded Tee 19 mm x 1/2" BSPF	45165	25	15	6.3
Threaded Tee 19 mm x 3/4" BSPF	45055	25	12	8.3
Threaded Tee 25 mm x 1/2" BSPF	45175	25	10	5.8
Threaded Tee 13 mm x 1/2" BSPM	45185	25	25	6.5
Threaded Tee 19 mm x 1/2" BSPM	45205	25	22	5.2
Threaded Tee 19 mm x 3/4" BSPM	45215	25	16	4.6
Threaded Tee 25 mm x 1/2" BSPM	45225	25	10	5.4
Threaded Tee 25 mm x 3/4" BSPM	45235	25	9	5.4
Increasing Tee 15 mm line x 16 mm branch	46305	25	27	7.1
Increasing Tee 15 mm line x 19 mm branch	46315	25	24	5.8
Increasing Tee 18 mm line x 19 mm branch	46325	25	20	5.5

Ordering Information - Crosses

Type	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
Cross 13 mm	44635	25	26	4.2
Cross 19 mm	44645	25	12	4.1
Cross 25 mm	44655	25	8	3.9



Tee



Threaded Tee Female



Threaded Tee Male



Cross



Elbows

A range of polypropylene Elbows and nylon Corner Elbows designed to control, disperse, slow and divert water through a low pressure irrigation system. Used in conjunction with low density poly (LDPE) tubing.

Features

- Tapered entry on all barbed fittings for ease of installation.
- Threaded Elbows for sprinkler systems.
- Range suits Metric tube sizes and common drip tube sizes.
- UV stabilised materials for long life.
- Operating pressure range up to 300 kPa.

Ordering Information - Elbows

Type	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
Elbow 13 mm	44835	25	75	6.7
Elbow 19 mm	44865	25	36	5.6
Elbow 25 mm	44875	25	14	5.8
Elbow 32 mm	44825	25	8	5.1
Threaded Elbow 13 mm x 1/2" BSPF	44955	25	28	8.5
Threaded Elbow 19 mm x 1/2" BSPF	44965	25	24	7.7
NEW Threaded Elbow 19 mm x 3/4" BSPF	45025	25	16	10.1
Threaded Elbow 25 mm x 1/2" BSPF	44975	25	16	6.7
Threaded Elbow 13 mm x 1/2" BSPM	44885	25	34	6.4
Threaded Elbow 19 mm x 1/2" BSPM	44905	25	36	5.8
Threaded Elbow 19 mm x 3/4" BSPM	44915	25	25	5.5
Threaded Elbow 25 mm x 1/2" BSPM	44925	25	17	6.2
Threaded Elbow 25 mm x 3/4" BSPM	44935	25	14	6.2
Reducing Elbow 16 mm x 15 mm	46155	25	50	7.4
Reducing Elbow 19 mm x 15 mm	46165	25	36	5.9
Reducing Elbow 19 mm x 18 mm	46175	25	35	6.3
Reducing Elbow 21 mm x 19 mm	46185	25	30	5.9

Ordering Information - Corner Elbows

Type	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
NEW Threaded Corner Elbow 19 mm x 1/2" BSPF	45015	10	26	6.8
Threaded Corner Elbow 19 mm x 1/2" BSPM	45005	10	28	6.9
NEW Threaded Corner Elbow 19 mm x 3/4" BSPM	44985	10	26	6.7
NEW Threaded Corner Elbow 25 mm x 3/4" BSPM	44895	10	22	5.9



Elbow



Threaded Elbow Male



Threaded Elbow Female



Threaded Corner Elbow Male

NEW

NEW

Threaded Corner Elbow Female



Applications

Home gardens, landscaping and commercially installed irrigation systems.

Accessories:

Ratchet Clamps
and Stainless
Steel Clamp.

Joiners

A range of polypropylene joiners designed to control, disperse, slow and divert water through a low pressure irrigation system. Used in conjunction with low density poly (LDPE) tubing.

Features

- Tapered entry on all barbed fittings for ease of installation.
- Range suits Metric tube sizes and common drip tube sizes
- UV stabilised materials for long life.
- Operating pressure range up to 300 kPa.



Ordering Information - Joiners

Type	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
Joiner 13 mm	44705	25	90	7.0
Joiner 15 mm	46005	25	60	6.6
Joiner 18 mm	46015	25	50	7.0
Joiner 19 mm	44715	25	40	6.1
Joiner 21 mm	46025	25	36	5.9
Joiner 25 mm	44735	25	20	6.3
Joiner 32 mm	44745	25	10	4.7

Ordering Information - Reducing Joiners

Type	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
Reducing Joiner 16 mm x 15 mm	46055	25	60	7.2
Reducing Joiner 19 mm x 13 mm	44805	25	50	6.2
Reducing Joiner 19 mm x 15 mm	46065	25	50	6.6
Reducing Joiner 19 mm x 18 mm	46075	25	44	6.3
Reducing Joiner 21 mm x 19 mm	46085	25	40	5.9
Reducing Joiner 25 mm x 13 mm	44765	25	32	6.8
Reducing Joiner 25 mm x 19 mm	44775	25	26	5.9
Reducing Joiner 32 mm x 25 mm	46095	25	12	4.6



Joiner



Reducing Joiner

Applications

Home gardens, landscaping and commercially installed irrigation systems.

Accessories: Ratchet Clamps and Stainless Steel Clamp.

