

Putting Water Where it Counts!®



Valves Green Back® & Purple Back®

Made in Australia

antelco.com

Green Back® Valves

On/off device to control the water flow in low pressure irrigation systems.

Features

- Simple on/off operation and straight through flow.
- Operating pressure range up to 300 kPa.
- Green Back® cap for standard irrigation applications.
- Purple Back® lilac cap easily identifies recycled water - not for human consumption.
- UV stabilised materials for long life.



Green Back® Valve



Purple Back® Valve

Applications

End of line flushing and manual on/ off flow control of submain and lateral lines. Vineyards, orchards, nurseries, greenhouses, landscaping and home gardens.

Ordering Information - Green Back® Valves

Base type	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
Green Back® Valve 13 mm (Shank OD 12.6 mm)	45505	20	25	9.4
Green Back® Valve 14 mm (Shank OD 14.0 mm)	45575	20	25	9.7
Green Back® Valve 15 mm (Shank OD 14.6 mm)	45555	20	25	9.5
Green Back® Valve 16 mm (Shank OD 15.7 mm)	45515	20	24	9.9
Green Back® Valve 18 mm (Shank OD 17.6 mm)	45565	20	10	10.2
Green Back® Valve 19 mm (Shank OD 19.0 mm)	45525	20	10	10.3
Green Back® Valve 21 mm (Shank OD 20.8 mm)	45535	20	10	10.5
Green Back® Valve 25 mm (Shank OD 25.0 mm)	45545	20	4	7.1

Ordering Information - Purple Back® Valves

Base type	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
Purple Back® Valve 13 mm (Shank OD 12.6 mm)	46505	20	25	9.4
Purple Back® Valve 14 mm (Shank OD 14.0 mm)	46575	20	25	9.7
Purple Back® Valve 15 mm (Shank OD 14.6 mm)	46555	20	25	9.5
Purple Back® Valve 16 mm (Shank OD 15.7 mm)	46515	20	24	9.9
Purple Back® Valve 18 mm (Shank OD 17.6 mm)	46565	20	10	10.2
Purple Back® Valve 19 mm (Shank OD 19.0 mm)	46525	20	10	10.3
Purple Back® Valve 21 mm (Shank OD 20.8 mm)	46535	20	10	10.5
Purple Back® Valve 25 mm (Shank OD 25.0 mm)	46545	20	4	7.1

Specifications - Green Back® and Purple Back® Valves

		13 mm, 14 mm 15 mm, 16 mm	18 mm, 19 mm 21 mm	25 mm
UV STABILISED MATERIAL	BODY STEM COVER SEAL	acetal polypropylene acetal -	acetal polypropylene acetal silicone rubber	acetal polypropylene acetal -
BASE/CONNECTION TYPE		barb	barb	barb



Threaded Valves

Threaded flow control valves for low pressure irrigation.

Features

- 1/2", 3/4" or 1" male threaded inlet.
- Simple on/off operation and straight through flow.
- Operating pressure range up to 300 kPa.
- Green Back® cap for standard irrigation applications.
- Purple Back® lilac cap easily identifies recycled water - not for human consumption.
- UV stabilised materials for long life.



Threaded Purple Back® Valve



Threaded Green Back® Valve

Applications

Irrigation from rain tanks, non-pressurised containers or pressurised systems up to 300 kPa.

Ordering Information - Green Back® Threaded Valves Male Thread

Base type	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
Green Back® Valve 13mm Barb x 1/2"	49005	20	22	9.8
Green Back® Valve 14mm Barb x 1/2"	49015	20	22	9.9
Green Back® Valve 15mm Barb x 1/2"	49025	20	22	9.8
Green Back® Valve 16mm Barb x 1/2"	49035	20	22	10.3
Green Back® Valve 13 mm Barb x 3/4"	46605	20	22	10.4
Green Back® Valve 14 mm Barb x 3/4"	46675	20	22	10.6
Green Back® Valve 16 mm Barb x 3/4"	46615	20	21	10.9
Green Back® Valve 18 mm Barb x 3/4"	46685	20	9	10.2
Green Back® Valve 19 mm Barb x 3/4"	46695	20	9	10.2
Green Back® Valve 21 mm Barb x 3/4"	46595	20	9	10.3
Green Back® Valve 25 mm Barb x 1"	46625	20	4	7.7

NEW

Ordering Information - Purple Back® Threaded Valves Male Thread

Base type	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
Purple Back® Valve 13 mm Barb x 1/2"	49105	20	22	9.8
Purple Back® Valve 14 mm Barb x 1/2"	49115	20	22	9.9
Purple Back® Valve 15 mm Barb x 1/2"	49125	20	22	9.8
Purple Back® Valve 16 mm Barb x 1/2"	49135	20	22	10.3
Purple Back® Valve 13 mm Barb x 3/4"	46705	20	22	10.4
Purple Back® Valve 14 mm Barb x 3/4"	46775	20	22	10.6
Purple Back® Valve 16 mm Barb x 3/4"	46715	20	21	10.9
Purple Back® Valve 18 mm Barb x 3/4"	46785	20	9	10.2
Purple Back® Valve 19 mm Barb x 3/4"	46795	20	9	10.2
Purple Back® Valve 21 mm Barb x 3/4"	46805	20	9	10.3
Purple Back® Valve 25 mm Barb x 1"	46815	20	4	7.7

NEW

Specifications - Threaded Valves

	1/2" MNPT	3/4" BSPM		1" BSPM
		13 mm, 14 mm 15 mm, 16 mm	18 mm, 19 mm 21 mm	
UV STABILISED MATERIAL	BODY STEM COVER SEAL	acetal polypropylene acetal -	acetal polypropylene acetal silicone rubber	acetal polypropylene acetal -
BASE/ CONNECTION TYPE	1/2" MNPT x barb	3/4" BSPM x barb		1" BSPM x barb



Antelco Group of Companies

LINCOLN
— Est. 1959 —
MOULDING THE FUTURE

ANTELCO®

Dawn



Antelco Australia
Antelco Pty Ltd ABN 50 008 062 708
Sales & Marketing,
Orders & Warehouse
Research & Development
PO Box 95, 131 Tolley Rd,
St Agnes SA 5097 Australia
+61 8 8334 4333
adelaide@antelco.com.au

Antelco USA
Antelco Corporation
Sales & Marketing,
Orders & Warehouse
886 Waterway Pl,
Longwood,
Florida 32750 USA
+1 407 331 0699
info@antelco.com

Antelco Europe
Antelco UK Limited
Sales & Marketing,
Orders & Warehouse
17a Chartmoor Rd,
Leighton Buzzard,
Bedfordshire LU7 4WG UK
+44 152 585 9990
orders@antelco.co.uk